



sanding discs with appropriate polishing pads, rotating brushes with sisal/leather belts, etc. are also suitable. Apply a second coat as required.

4. Equipment cleaning: Clean immediately after use with BIOFA Thinner 0500.

Important:

Be sure to test product before proceeding! Ensure sufficient fresh air circulation when processing and drying the products!
Do not use below 16°C!

Recommended Equipment:



1. **009984 / 009974 / 009988** Pad white Ø 150mm / pad white with adhesive fleece Ø 150mm / pad white Ø 410mm for buffing
2. **0500** BIOFA Thinner for cleaning the working equipment

Drying:

Can be walked on and reworked after approx. 12-16 hours. May be carefully used after 2 days and is completely durable after 7-10 days (20°C/50-55% rel. humidity).

Consumption/yield per coat

10-15 ml/m² bzw. 60-100 m²/l.

Maintenance:

Walk carefully during the first two days. Cover walking areas with paper or cardboard. Initially, clean only dry. After approx. 4 weeks, following a mist-damp cleaning with NACASA 4010, Care Emulsion NAPLANA 2085 or NAPLANA Plus anti-slip 2086 can be applied. Further maintenance cleaning and care is carried out as required. Signs of wear after prolonged use require refreshing with BIOFA Wax Balm 2063

Storage:

Keep cool, dry and properly sealed. Skin formation possible. Remove before using again.

Container:

Interior painted metal container

Disposal:

Liquid product residues and containers which have not been emptied and cleaned should be taken to a collection point for used paints/lacquers or disposed of in accordance with local/national regulations. Small residual quantities and soaked working materials can be disposed of with household waste after drying out. Only empty and cleaned containers should be recycled.

AVV waste code according to European waste list: 08 01 12

Safety instructions:

Store work materials and clothing soaked with product in airtight metal containers or soak with water and allow to dry spread out on a non-flammable surface - (risk of spontaneous combustion!) The product itself is not self-igniting. Keep out of the reach of children. If medical advice is needed, have packaging or label ready. Do not get in eyes, on skin or on clothing. Provide adequate exhaust ventilation and respiratory protection when spraying. Ensure adequate skin protection. Wear fine dust mask during grinding work. A typical odor of the natural raw materials is possible.

Safety data sheet available on request!

VOC labeling law. Decopaint directive and ChemVOCFarbV:

EU threshold (Cat. A/i): 700 g/l (2010)
2063 contains max. 1 g/l VOC

GISCODE: Ö 10+